

HG 530-A Universal Kit



The HG 530-A Universal Kit is suitable for various professional hot air applications. It includes the powerful HG 530-A heat gun as well as a pressure roller, spoon reflector, wide slot nozzle, tube nozzle and solder reflector.

- + Powerful in work mode, power-saving in Eco-Mode
- + Infinitely variable digital temperature control
- + Ergonomically designed, balanced, soft handle
- + Various functions for industrial applications
- + Temperature and air stage storage

Technical Data

Voltage	100 V; 120 V; 230 V	
Frequency	50/60 Hz	
Power	1300–2300 W	
Temperature	80–650 °C	176.0–1202.0 °F
Temperature setting stepless	Yes	
Air flow (20°C)	200–550 l/min	7.06–19.42 cfm
Stepless air volume adjustment	Yes	
Eco-Mode	Yes	
Display	Yes	
Outdoor use	No	
Nozzle connection ø	35.5 mm / 1.4 in	
Length	250.0 mm	9.84 in
Width	80.0 mm	3.14 in
Handle diameter	45 mm	1.77 in
Weight	0.75 kg	1.65 lb
Power cable length	2.0 m	6.56 ft
Noise emission level	67 dB (A)	
Conformity mark	CE	
Protection class	II	
Country of origin	CN	

Scope of delivery

Spoon reflector (ø 35.5) 40 x 35 mm; Tubular nozzle (ø 35.5) ø 6 mm, 75 mm; Wide slot nozzle (ø 35.5) 25 x 3 mm; Solder reflector (ø 35.5) 13 x 5 x 10 mm; Pressure roller 30 mm, ABS



Configure product



Find accessories

HG 530-A Car Wrapping Kit



The Weldy HG 530-A Car Wrapping Kit has everything professional car wrappers need: HG 530-A heat gun with Eco-Mode, digital temperature and blower control, 5 meter long cable and practical air inlet covers.

- + Intelligent Eco-Mode saves energy and money
- + Heat protection for increased safety
- + Air inlet covers ensure air supply
- + Increased flexibility when working thanks to its 5 m (16.4 ft) cable
- + Individual parameter control and recall ability

Technical Data

Voltage	120 V; 230 V	
Frequency	50/60 Hz	
Power	1500–2300 W	
Temperature	80–650 °C	176.0–1202.0 °F
Temperature setting stepless	Yes	
Air flow (20°C)	200–550 l/min	7.06–19.42 cfm
Stepless air volume adjustment	Yes	
Eco-Mode	Yes	
Display	Yes	
Outdoor use	No	
Nozzle connection ø	35.5 mm / 1.4 in	
Length	250.0 mm	9.84 in
Width	80.0 mm	3.14 in
Handle diameter	45 mm	1.77 in
Weight	0.75 kg	1.65 lb
Power cable length	5.0 m	16.4 ft
Noise emission level	67 dB (A)	
Conformity mark	CE	
Protection class	II	
Country of origin	CN	

Scope of delivery

Heat protection; Air inlet cover set (2 units)



Configure product



Find accessories