

+++ **Primer** Pro 1L – ISO Base+++ (600-PMR1000PRO – 600-PMR250PRO)



- **Intro:**

Primer PRO is a ISO based primer for use a non-absorbent-surface where you apply Cover Styl' interior film.

- **Question 1**

Example of surface where to use it?

melamine, treated and massive wood (not textured), painted surfaces but also on surfaces that have undergone treatments such as galvanizing and anodized. It can be uses also on surfaces painted with synthetic polymers such epoxy coating, polyurethane, powdered paint and varnishes.

- **Question 2**

Where to use it?

perimeter and edges or stress areas with a minimum of 0,5 mm thickness

- **Question 3**

How to apply it?

use the Primer+ stick (600-PMR40) or a specific solvent applicator.

- **Question 4**

Which is the drying time?

2 min. (apply Cover Styl' within 5 hour)

- **Question 5**

Which is the stock life: 13 months if you're careful to seal the bottle after each use.

- **Question 6**

Which are the advantages of this primer?

1 Drying period is very short, at just 2 minutes. This means that once you've applied the primer on your surface, you can go ahead and start installing your Cover Styl'.

2 Its eco-friendly and healthier for you as an installer, as it contains isopropyl alcohol, rather than solvent. It's less harmful when inhaled.

3 It leaves no smell in the environment.

4 This primer is optimal for usage on galvanized and anodized surfaces.